ON THE INSTRUMENTED MONITORING OF UNDERSEA VEHICLES

M.R. Nayak

National Institute of Oceanography, Goa-403 004. INDIA

ABSTRACT

ring a viable tool with a special way of the control of the contro

INTRODUCTION

the control to the marine environment and unmanned undersea unmanned undersea are personal senses are the worksite in order to the task, the use of a relicted are paticularly undersea work and tasks for the following

restional endurance, into 4 equipment costs, restrained ability in restrained areas (without restrained personnel), and list dieng problems (smaller restrained by the second of t

which may collect

relevant undersea vehicle data more cost-effectively, more reliably, independently of environmental conditions. A number of methods and systems are existing at present. Some reasons for their lack of success are:

- available functional failure detection methods,
- unreliable or vulnerable instrumentation (which cannot be repaired/replaced on-site).
- time-consumming, inefficient undersea data analysis routines.

The current state-of-art of detection/monitoring methods available for automation/ instrumentation is discussed in the paper.

METHODOLOGY

The general parameters that monitored and their tasks fall into four basic groups viz; navigation (visual, compass heading, depth sonar); scientific instrumentation recorder, samplers, radiometer, coring devices & releasers) (2); life support (cabin temperature, pressure, oxygen, CO, %); operational (ballast air supply, battery voltage, thruster function & electrical system) [3]. The operational constraints of such undersea system include system power requirements, propulsion system efficiency, power transmission voltages, heat losses [4], drags, handling equipment and vehicle power plant dimension.

An important consideration in achieving safe, reliable, long- term undersea operational system in a marine environment is the proper design, construction and routine monitoring of the performance. While no monitoring programme can guarantee that all

defects or degradation can be deleted in the undersea vehicle, it must provide sufficient information leading towards the implementation of routine maintenance programmes. This includes considerations indicating whether or not further inspection (or remedial, restorative measures) are needed.

More than 180 unmanned vehicles are in operation (in the world), about 90 operated by commercial companies, the rest being with research organisations, navy and universities. These underseavehicles are capable of:

- inspection/observation,
- recovery of tools,
- cleaning, brushing & chipping,
- cutting cables,
- attach lines with ease, and
- connect hydraulic lines & valves.

The advantages are:

- real time data coverage,
- high endurance, and
- depth capabilities.

Monitoring of undersea vehicles require system development including selection design of modules/sub-systems in various fields of technology /5/ such as, materials, components, navigation.

- * Materials: The continuing development of solid-state devices (VLSI) has areas of undersea opened new applications. These include μP, and multiplex systems, control monitoring components: all of which may be made pressure- tolerant (& can be installed in lightweight, oil-filled pressure- cmpensated containers for operations to all depths in the sea. Electrical application is further strengthened by the development of the chemistry, packaging and electrohandling techniques required to provide safe high-energy-density batteries.
- Components: Advancement in the field of solid-state electronic components has brought-in major improvements in the packaging of unersea electronic systems. The basic characteristics of pressure- tolerant electronics (PTE) (electronics not protected from depth pressure) is an advantage. PTE systems use liquid-filled, pressure-equalised containers which provide unlimited freedom of choice in container size, shape and materials.
- * Sensors: The acoustic, optical and magnetic sensors have contributed to the achievements of undersea vehicles. These provide a means to find the Jorksite, provide for inspection and

documentation of the characteristics of the site, and means to monitor & control the tools during operations.

* Navigation: The navigation subsystems are an important part of undersea monitoring instrumentation since they provide the means of finding a precise location, and a means of returning to same work- site on repeated excursions.

MONITORING-MISSION

The goal of monitoring campaign is to assess the proper functioning of all the modules in the undersea vehicles: and to replace one or several failed modules on-board the vehicle.

- a) Instrumented Monitor: is an un-manned monitoring vehicle which can perform:
 - the rendezvous, and the docking with the operational vehicle,
 - perform robotic operation
 (with servo-controlled arm),
 - produce and transmit video-images during the grasp and the other operations.

These functions provide a wide range of in-situ capabilities. The important mission in monitoring requires great reliability. The monitoring vehicle shall also carry spare modules for whole servicing campaign.

b) The operational vehicle: is the vehicle which has been assigned specific tasks to perform in the undersea environment. This segment is assisted by ship-control whose main duties, beyond the classical function of control and localisation, are to yield to the proper monitoring of the necessary parameters for navigation and retrieval, and sequences of orders for teleoperations.

In the context of oceanography, remote data acquisition instruments are available today. These instruments range from simple mechnaical devices for seabed or water sampling, to sophisticated intelligent devices for monitoring and processing a number of ocean parameters. Equipments for remote control and undersea monitoring has a crucial reliability requirement. The application of growing importance is

onitoring of undersea vehicles, sost crucial being the "status oring":

"stor operations should be additioned to take up precisely edesired position requires: recision sensor'; mote monitor function; duction in the number of tectrical connectors'; tection/monitoring of hydraulic essure and temperature;

ly, this indicates the necessity

tenomous watch-dog actions (and tection of malfunction), mitoring of system parameters and indicate system conditions).

rajor objectives of developments of ological innovations are, (taking consideration the various commental considerations): crease in flexibility, provements in reliability, cancement of safety factor, cimization in instrumentation,

relopment of new materials, velopment of new devices and collities, velopment of new process changes, belopment of new system, and relopment of new software.

be [6] briefly fellowing can ified as the area involved: highly οf alization ..!ligent monitoring system; 'eDident (with robot agresis and recovery functions; precision *rabiob production chnology; micro-sensor with telligent gh sensitivity and reliability

the activities indicates ved in the process monitoring for undersea vehicle. A wide ty of methods are available to scheduling and planning. will have to be re-run dically because the conditions inevitably . change. ation is used to determine bling strategies and floor layout. general, the technology οf foring - including process and iter handware, software is basic rapidly, а standing of Systems Issues remain these issues include 'plete: ling, scheduling, and control of work. These are complicated by randomness in the undersea environment, particularly due to instrument failures and uncertainty/variability in monitoring requirements.




Fig. 1, INSTRUMENTED MONITORING CONCEPT

CONCLUSION

of research main thrust in instrumented monitoring of undersea complicated by vehicles is particularly oriented environment, towards mechnical failures and uncertainty, and variability in system requirements. In order to achieve the required number of operating status, it is certain that a microprocessor-based design will be required. Bearing in mind the need for high reliability of certain module functions a practical design concept is suggested, keeping in mind greater flexibility for future design changes and using off-the-shelf components. The tasks suggested are (on priority commands under interrupt routine):

- power-on initialisation,
- error detection/correction,
- monitor scan sequence,
- status feedback,
- self-test procedure
- power-down procedure.

The continous monitoring of information is especially important as the deployment of undersea vehicle progresses in the operational phase. It can also be pointed out that efficiency can be increased by:

- reducing operational times, and

improving technological capability.

ACKNOWLEDGEMENTS

The author wishes to thank Dr.Florian Schirmer, Institute fur Meereskunde (PRG), Dr.B.N.Desai, Director, and Dr.H.Desa, Head MICD for the useful discussions, constant encouragement and advice during the study.

REFERENCES

- WILLIAMS JJE, "A High integrity subsea control and monitoring system." Cranfield Institute of Technology, USA.1984.
- Operational Guidelines for ROVs Report of the ROV Subcommittee of the Undersea Vehicles Comm. MTS, Washington DC, USA. 1984.
- SIMON PETER A. Operational Consideration for a Scientist-Piloted Research Submersible. Proc.ROV'87 San Diego, CA, USA. p79-82.
- NAYAK MR.On the operational aspects of Subsea Systems. Proc.ROV'87.San Diego,CA,USA p75-78.
- Undersea Vehicles Directory: 1985, Busby Associates, Inc; Arlington, VA; USA.
- IWATA K.Artificial Intelligence and CAD/CAM. Journ.of Japan Soc Prec.Engg. 49(10): 1448-1449, 1983.